

**METHOD AND APPARATUS FOR AUTOMATICALLY APPLYING
A FLYING SPLICING TAPE TO A ROLL OF SHEET MATERIAL**

Abstract of the Disclosure

5 A method and apparatus for automatically applying a flying splicing tape
to a roll of sheet material. The roll of sheet material is defined by a width and
includes an outer-most layer. With this in mind, the method includes lifting a
portion of the outer-most layer away from a remainder of the roll. The lifted
portion is then cut to form a leading edge that is otherwise spaced from a
10 remainder of the wound roll. To this end, the cut is made at a defined spacial
location along the outer-most layer such that the leading edge is radially aligned
with a defined application line relative to a circumference on the wound portion
of the roll. In other words, when the outer-most portion is subsequently wound
back onto the roll, the leading edge will be aligned with the defined application
15 line. The splicing tape is then applied to the wound portion of the roll at the
defined application line, such that the splicing tape extends across at least a
portion of the width of the roll. In one preferred embodiment, the splicing tape
is applied in a straight fashion relative to an axis of the roll. Finally, the leading
edge is adhered to an outer surface of the splicing tape. More particularly, the
20 leading edge is positioned relative to the splicing tape such that the outer-most
layer covers a first section of the splicing tape, whereas a second section of the
splicing tape remains exposed. In another preferred embodiment, the applied
splicing tape is cut to form a trailing end that is substantially aligned with a side
of the roll.